



FLOCON-RM

PRODUCT DESCRIPTION:

FLOCON RM is a Factory Formulated, Premixed, Preblended cementitious High strength concrete / Mortars formulations designed using German Technology for various Decorative concrete/Mortar /Precast / GFRC/TRC/Floorings /Polished concretes, Thin section High performance Overlays applications

PURPOSE:

For using in Cementitious Decorative Precast, Thin section Overlays ,Polished /Stamped Concretes applications.etc

USAGE:

Its a Blend of various Cementitious, Pozollans & Admixtures to achieve various decorative finishes ,strength,workability etc

ADVANTAGES:

- Flow Con RM is Capable of delivering excellent surface finish in thinner sections (min 6mm)
- It can easily flow in to the complex formwork or heavily reinforced sections in Precast applications
- The Mix design concept applied to the dry mix products ensures that each formulation is robust,& functional in a normal site working conditions
- Reduced Labour requirements,due to ease of placement & finishing
- Reduces impact on environment due to reduce in noise pollution due to elimination of vibration for compaction
- Can be offered in various earthen Oxide Based UV & IR Light Fast Stable Colours
- Formulations can be developed to achieve compressive strengths ranging from 45Mpa till 100Mpa
- Improved out put in a Pre cast environment for pre cast elements & Decorative floorings
- Labour Savings due to reduction in Placing & finishing time
- When used as a screed can offer superior performance against conventional site mixed sand,cement mortars.screeds
- Manufactured in a controlled factory environment to give a uniform consistent results
- Its formulations can be tailor made to suit the specific site/job requirements

Uses:

- Decorative Precast, Decorative Thin section Polished concrete thin section Overlays
- Decorative Floorings
- Industrial Patch Repairs
- Premix GFRC (excluding the AR Glassfibers) for on site castings/ mouldings

Grades Offered : Flocon RM is offered in various Grades based on application Requirements such as Flocon 60, Flocon 80,Flocon FRR

Application Guidelines:

- Based on the grades offered the respective water to powder ratios are offered to achieve the optimum performance from the product.
- For detailed application requirements, please get in touch with us for detailed usage guidelines.

Storage:

Store in a cool & dry place away from Direct sunlight with proper sealed Bags

Shelf Life:

Minimum 3 Months if stored in a cool & dry place away from direct sunlight,water,moisture.

Packing : 40Kg Woven bags with Liner

Note: FLOCON Premixes for Polished concrete flooring are formulated to be perfectly homogeneous in appearance. But sometimes the physical act of spreading and smoothing, along with the sanding process, will result in optical variations in the appearance of the floor even though it is very flat. The aesthetic appearance of the floor that is created is subject to possible technical and artistic tolerances. Variations in the overall finished appearance are an intended effect and should be expected. Always install an adequate number of properly located test areas, including the processing, to determine the suitability and aesthetic value of the products for the intended use. The finished floor achieves its published mechanical properties after 28 days

Disclaimer

The information contained herein is believed to be accurate and is offered in good faith for the guidance of the consumer. We cannot accept any responsibility for errors in, or misinterpretation of the information contained in this brochure. In view of our constant endeavor to improve the quality of our products, we reserve the right to alter or change the specifications without prior notice

For Details Contact :

TEJ INNOVATIVE PRODUCTS B-4,P-10,ABOVE I.O.BANK,H.F.S.ROAD, JOGESHWARI(EAST) MUMBAI-400060 INDIA

Tel. : (O):0091-22-28246536 / Cell:0091-9821170321 / 7977169080

Email: tejas_t@yahoo.com OR tejas60@gmail.com